

VENKRAFT PAPER MILLS



Semi Sack Kraft Paper

- High Strenght Kraft Paper
- Basis Weights 50 to 180 GSM





At a level of almost 100,000 tons annually, Venkraft is one of the largest producers of containerboard/kraft paper/semi sack kraft paper in Southern India. Our Four-driner Combined Paper Machine has all the requisite equipments to manufacture the following.

Machine Finished Kraft Paper

• GSM Range: 50 to 180 grams/m²

Machine Deckle: 275 to 285 cms. / 108 to 112 inches

Colour Shades: Natural, Golden Yellow.

BF Range: 18 to 24 BF

Semi Sack Kraft Paper is typically used in the manufacture if shopping bags, grocery bags, paper bags with or without printing etc.





Semi Sack Kraft (TECHNICAL SPECIFICATIONS)

- High Strenght Kraft Paper
- Basis Weights 50 to 180 GSM
- BF 18 to 28

Parameter	Unit	Value
Stretch	% mm	3-4
Cobb Top	GSM	40-45
Cobb Bottom	GSM	45-50
Moisture	%	6-7%
		Tolerance:± 3%

Please note:

- 1. The tolerances are based upon 95% confidence limit and on laboratory results of random samples from mill.
- 2. The specifications are subject to change without any prior notice.
- 3. Moisture is measured on oven dry method.
- 4. Paper board Machine Deckle: 275 cms to 285 cms.

Venkraft Paper Mills Pvt Ltd., Unit – 1

Kraft Unit - Factory Address: 10th K.M., Kelamangalam Road, Aggondapalli Village, Hosur-635110,

Tamil Nadu, India.

<u>Domestic Marketing Contacts:</u> Email: <u>marketing1@venkraft.com</u>, Marketing Head (+ 91 9442229773),

Tamil Nadu Coordinator (+91 7867004081). Karnataka Coordinator (+91 9600772211).

Export Marketing Contacts: Email: exports@venkraft.com, Export Coordinator (+ 91 8220005701).

www.venkraft.com